

WALL PUTTY



HARIKRISHNA
CONCRETE SOLUTIONS
A SUPERIOR QUALITY MATERIALS

HK WALL PUTTY is a specially formulated product based on polymer modified white cement blended with special additives to be used as putty, filler, and sealer, on concrete / mortar walls and ceiling. HK WALL PUTTY renders to the surface smooth bright white coating suitable for over coating giving a durable and smooth finish on the walls. It also used for interiors & exteriors.



ADVANTAGES

EASY TO USE AND APPLY

UV RESISTANCE

SUITABLE FOR INTERIOR & EXTERNAL WALL

WATER RESISTANT

EXCELLENT ADHENSION & DURABILITY

COST EFFECTIVENESS

EXCELLENT WHITENESS & SMOOTH FINISH

TECHNICAL SPECIFICATIONS

PARAMETERS	SPECIFICATIONS
COLOUR	White Powder
HARD DRYING	6 – 8 HR
Compressive Strength	8.5 Mpa
Flexural Strength	2.1 Mpa
Water REQUIREMENT	40 – 45 % MIXING OF PAINT FOR APPLICATION
Pot Life	2 TO 3 HR
Applied thickness each coat	1.5 mm
Coverage	12-15 Sq.ft/kg depending on wall finish

